

## Contactors




### CWC0 - Compact Contactors

- Complete line from 7 to 22 A (AC-3)
- Quick mounting on 35 mm DIN rail or screw mounting
- Built-in auxiliary contacts up to 16 A
- Low-consumption DC coils, allowing direct connection to PLCs
- Direct mounting on RW17 overload relays
- Same dimensions (AC or DC coil) for models up to 16 A



### CWB - Contactors

- Compact solution up to 38 A and 45 mm wide
- Built-in auxiliary contacts 1NO + 1NC
- Low energy consumption DC coils allow direct drive of the contactors via PLCs, inverter outputs or soft-starters without requiring an interface relay
- More compact assemblies of motor starters
- Developed according to IEC 60947 and UL 508 international standards
- Wide range of accessories



### CWM - Modular Contactors


- Complete line from 9 to 800 A (AC-3)
- 3-pole and 4-pole contactors
- Quick mounting on 35 mm DIN rail or screw mounting
- Contactors available in several command voltages and frequencies (AC or DC)
- Direct mounting of contactors on overload relays up to 105 A
- Wide range of accessories
- Easy connection busbars for star-delta or reversing starters interconnection, allowing fast mounting and reducing space

## Overload Relays



### RW - Thermal Overload Relays


- Current setting range from 0.28 to 840 A
- Tripping class 10
- Versions allowing direct mounting to compact contactors/contactors, screw mounting or DIN rail mounting with accessory
- Adjustable multifunction key with HAND, AUTO, H or A functions
- Auxiliary contacts 1NO + 1NC



### RW\_E - Electronic Overload Relays

- Three-pole electronic overload relay with selectable trip class: 10, 20 and 30
- Phase loss protection (time delay <5 seconds)
- Phase unbalance protection (>40% between phases)
- Temperature compensated
- Manual or automatic reset
- Direct mounting on CWB9...38 and CWM9...105 contactors
- Allows individual mounting with accessories
- Auxiliary contacts 1NO + 1NC

# Motor Starters and Protective Circuit Breakers



## MPW - Motor Protective Circuit Breakers

- Motor-protective circuit breakers with high short-circuit breaking capacity up to 100 A ( $U_e \leq 690$  V)
- Compact solution up to 40 A and 45 mm wide and up to 80 A 54 mm wide
- Motor start and protection up to 40 HP at 220 V and 75 HP at 380/440 V
- Adjustable thermal releases to protect the motor against overload
- Magnetic releases for short circuit protection fixed at 13xIn



## PESW - Enclosed Motor Starters

- Three-phase contactors in thermoplastic enclosures up to 40 HP at 220 V and 75 HP at 380/440 V and 600V, and single-phase contactors
- Star-delta starters in thermoplastic enclosures up to 20 HP at 220 V and 40 HP at 380 V
- Star-delta, reduced-voltage and series-parallel starters in metallic enclosure starting from 15 HP

# Relays and Pushbuttons



## RTW, ERWT AND RPW - Electronic Relays

- ED status indicators
- Simple configuration and operation
- Adjustments via external selectors
- High-reliability contacts
- Excellent accuracy, repeatability and noise immunity
- Mounting on DIN rail or screw mounting
- Compact enclosure 22.5 mm and 17.5 mm wide
- Available models:
  - Timers: simple function and timing (RTW17), multi timing (RTW-MAT/MBT) or multifunction (ERWT)
  - Voltage monitoring relays: single monitoring (RPW)



## CSW - Pushbuttons, Selector Switches and Pilot Lights

- Developed for different applications, harsh and industrial environments
- Degree of protection IP66
- Illumination blocks with integrated LED (high efficiency)
- Quick and easy mounting system
- High-reliability auxiliary contacts
- Wide range of accessories

V.J. Pamensky Canada Inc.  
64 Samor Rd.  
Toronto, ON  
M6A 1J6

1 (877) PAMENSKY (726-3675)  
[www.pamensky.com](http://www.pamensky.com)

